

FLUSH PANEL DOORS



**EXP, EXP BAL 12.5,
PAINT PLY**

HONEYCOMB CORE EXTERNAL

EXP

STANDARD SIZE	\$
2040 x 720 x 35	96
2040 x 820 x 35	96
2040 x 870 x 35	110
SPECIAL SIZES	\$
Up to 2040 x 820 x 35	152
Up to 2130 x 920 x 35	203
Up to 2400 x 1200 x 35	278
Up to 2040 x 820 x 40	171
Up to 2130 x 920 x 40	222
Up to 2400 x 1200 x 40	297

SOLID CORE EXTERNAL

EXP

PAINT PLY

STANDARD SIZE	\$	\$
2040 x 820/770/720/620/520 x 35	174	210
2040 x 870 x 35	185	-
2040 x 920 x 35	216	-
2040 x 820 x 40	266	-
2040 x 920 x 40	313	-
2340 x 820/770/720/620/520 x 35	206	-
2340 x 870 x 35	266	-
2340 x 920 x 35	278	-
2340 x 820 x 40	413	-

SPECIAL SIZES

\$

\$

Up to 2040 x 820 x 35	236	250
Up to 2130 x 920 x 35	287	286
Up to 2400 x 1200 x 35	350	404
Up to 2040 x 820 x 40	266	294
Up to 2130 x 920 x 40	313	370
Up to 2400 x 1200 x 40	413	476

BLOKDOOR EXTERNAL	EXP	PAINT PLY
STANDARD SIZE	\$	\$
2040 x 820 x 35	200	-
2100 x 920 x 35	243	-
2100 x 1200 x 35	-	-
2400 x 920 x 35	-	-
2400 x 1200 x 35	414	-
2040 x 820 x 40	257	-
2100 x 920 x 40	267	-
2100 x 1200 x 40	-	-
2400 x 920 x 40	-	-
2400 x 1200 x 40	472	-

BLOKDOOR CUT DOWN CHARGE	EXP	PAINT PLY
ADD TO STANDARD DOOR PRICE	\$	\$
	+26	+26

SPECIFICATIONS

Door construction	Honeycomb core.	Solid core.	Blokdoor core.
Skin	EXP External Primed skins.	EXP External Primed skins or Plywood.	EXP External Primed skins or Plywood.
Trimming	5mm from top, bottom and each stile.	5mm from top, bottom and each stile.	Blokdoor Core (Laminated Timber Core) no limitations to trimming.
Approx. weight	Honeycomb core – 16kg (Based on 2040 x 820 door).	Solidcore – 35kg (Based on 2040 x 820 door).	Blokdoor – 35kg (Based on 2040 x 820 door).
Pre-finishing & installation	Flat, semi-gloss or satin paint should be applied to door surfaces.	Gloss, flat, semi-gloss or satin paint should be applied to door surfaces.	Do not use this door in situations that require a high quality paint finish. This door has an open grain at the top and bottom due to its construction using a laminated softwood core-plate infill. 75mm minimum screws must be used for hinging.
	Light reflective colours should be used on all doors exposed to direct sunlight. Entrance doors must be installed in weather protected openings to reduce the effects of weather exposure. Refer to – Door Care and Maintenance recommendations. Failure to adhere to these recommendations will void warranty.		
Hinges	Doors measuring up to 2040 x 920 require a minimum 3 hinges. Doors over and above this size require 4 hinges.		
Primed	Primed skin, excludes door edges.		
Warranty	5 years – Terms and conditions apply – refer to Warranty and Terms and Conditions of Sale.		
Special sizes	Prices and lead-times upon application. These doors will be Made to Order. All honeycomb doors which exceed 920mm will require a 110mm Laminated Frame – Refer to Value Added Services and Extras for pricing.		
Made to Order (MTO)	Made to Order (MTO) doors including value added services applied to doors may only be cancelled on day of ordering. For further information contact Corinthian Customer Service.		
Note	All prices exclude GST. All sizes are nominal and in millimetres. Door furniture pictured on the doors is sold separately. All doors depicted are professionally finished. Doors are supplied raw.		

FEATURES

